




The XL was designed from the outset to offer maximum security and reliability.

XL features three hooks, two steel anti lift bolts and the option of either two or four roller cams for compression and smooth operation.

Every XL lock is extendable top and bottom for maximum flexibility and combined with Fullex high security shootbolts, the XL French door system is fully capable of meeting PAS24 requirements.

- Secured by Design
- PAS23/24 tested
- Three opposing steel hooks and two steel anti lift bolts
- Two or four roller cams
- Dual or single spindle options
- Easily reversible latch
- Latch hold back snib on lock faceplate
- One piece or individual keeps
- Extendable top and bottom as standard



www.fullex-locks.com



XL is available in a range of lock configurations and can be used with either one piece or individual keep sets.

The XL's attractive silver finish is also corrosion resistant to neutral salt spray in excess of BSEN1670 Grade 4, giving peace of mind to hard pressed fabricators and consumers.

Various 3 hook XL lock centres are available, with either 2 or 4 roller compression cams.

Other locks available include XLSL slave lock, XL4R centre hook, latch and 4 roller or XL2R2M centre hook, latch, 2 roller, 2 mushroom cams.

Technical Data

Corrosion Resistance
BSEN1670 Grade 4 (240 hours)

Cyclic Operation
Cycle tested to 100,000 cycles

Materials


Top And Bottom Hook
Chrome plated A3 hardened cast steel

Anti Lift Bolts
Chrome plated A3 hardened rolled steel

Centre Hook
Dacromet coated A3 sintered steel

Faceplate And Gearbox
Mild steel, Zinc and clear passivated or 44mm White Aluminium powder coated

Roller Cams
Mild steel, Zinc and clear passivated



www.fullex-locks.com